

<b>Test</b>	<b>Units</b>	<b>110 Minimum</b>	<b>110 Maximum</b>	<b>110 Typical</b>	<b>250 Minimum</b>	<b>250 Maximum</b>	<b>250 Typical</b>
<b>Viscosity ASTM D 445</b>	<b>cST @ 100 C cST @ 40 C SUS @ 100 F</b>	<b>4.1</b>	<b>4.5</b>	<b>4.3 22 112</b>	<b>7</b>	<b>7.4</b>	<b>7.2 49 250</b>
<b>Viscosity Index ASTM D 2270</b>				<b>102</b>			<b>107</b>
<b>Density – ASTM D 1298</b>	<b>g/cc @ 60 F lbs/gal @ 60 F</b>			<b>0.865 7.4</b>			<b>0.871 7.4</b>
<b>API Gravity – ASTM D 287</b>	<b>API @ 60 F</b>			<b>33.9</b>			<b>33</b>
<b>Color – ASTM D 1500</b>			<b>1</b>	<b>&lt;0.5</b>		<b>1.5</b>	<b>&lt;1.0</b>
<b>Flash Point, COC ASTM D 92</b>	<b>F</b>	<b>360</b>		<b>390</b>	<b>450</b>		<b>470</b>
<b>Pour Point – ASTM D 97</b>	<b>F</b>			<b>-15</b>			<b>-12</b>
<b>Total Acid Number</b>	<b>mg KOH/gm</b>			<b>&lt;0.01</b>			<b>&lt;0.01</b>
<b>Total Sulfur – ASTM D 3120</b>	<b>wt %</b>			<b>0.02</b>			<b>0.02</b>
<b>% Saturates – ASTM D 2007</b>	<b>wt %</b>			<b>90.5</b>			<b>92</b>
<b>Total Ash Content ASTM D 482</b>	<b>wt %</b>			<b>&lt;0.001</b>			<b>&lt;0.001</b>
<b>Crackle Test – Trace Water Chevron Test Method 350</b>				<b>PASS</b>			<b>PASS</b>
<b>Odor</b>				<b>None</b>			<b>None</b>
<b>Appearance</b>				<b>Bright &amp; Clear</b>			<b>Bright &amp; Clear</b>